

SPECIFICATIONS
VIBRATION METER 2040:

Sensor	:	Piezo-electronic Accelerometer with built-in charge amplifier in Stainless Steel body.
Measurement Ranges:		
Velocity	:	0-199.9 mm/sec or 0-19.99 mm/sec True RMS
Displacement	:	0-1999 microns or 0-199.9 microns Pk-Pk
Frequency Range	:	10Hz-1kHz (600-60,000 Cycles per minute)
Battery	:	4 X AA alkaline cells
Display	:	3 % digital LCD with Lo Batt. Indication
Temperature range	:	0-45 Deg C upto 90% humidity (non-condensing)
Dimensions	:	175 (L) x 70 (W) x 27 (D) mm.
Weight	:	400 gms approx, including battery
Standard Accessories	:	Sensor with 2m lead, Touch Probe, Magnetic base, AC Charger, Folio type carrying case, Operation Manual

Marketed by **ABE** (Accurate Balancing Equipment)

5 UK Indl. Est. Behind Durian Furniture, opp Oswal park,
 Pokharan, Road no.2, Thane (W) 400 602 Maharashtra, India,
 Tel:- 022- 21737777 / 78 / 79 Telefax:- 022- 21737788

Email :- admin@accuratebalancing.com / sales@accuratebalancing.com / contact@accuratebalancing.com